HOSHIZAKI





UNDERCOUNTER SERIES

> RTC-150SDA

COUNTERS

- Slimmest compressor in its class, saving up to 20% of space
- Stainless steel finishing allows the worktop to be used as a food preparation area
- Easy access or removal of compressor for efficient maintenance

depth 750mm

refrigerator > **RTC-120SDA** > **RTC-150SDA** > **RTC-180SDA**
freezer > **FTC-120SDA** > **FTC-150SDA** > **FTC-180SDA**

depth 600mm

refrigerator > **RTC-120SNA** > **RTC-150SNA** > **RTC-180SNA**
freezer > **FTC-120SNA** > **FTC-150SNA** > **FTC-180SNA**

In Any Busy Operation, The GOLDLINE Adheres To Practical Sanitary Guidelines And Are Easy To Clean With:



detachable gasket



easy access to removable air filter



round corners



light and durable door handle



E7 code tells "clean air filter" message

HOSHIZAKI





REACH-IN SERIES

> HRE-127B

CABINETS

- Heated front frame of freezer cabinet with insulation prevents condensation build-up
- Scheduled evaporator defrost cycle reduces buildup of ice, maintaining energy efficiency
- Uses DC fan motor - generates less heat compared to conventional AC motor in other by 80%

refrigerator > **HRE-77B** > **HRE-127B** > **HRE-147B** > **HRE-187B**
freezer > **HFE-77B** > **HFE-127B** > **HFE-147B** > **HFE-187B**

While Understanding The Need For All Units To Be Easy To Use And Easy To Service, GOLDLINE Units Are Fitted With:



removable refrigerator system (reach-in)



caster option




auto-close doors



gastronome option



compact slide out refrigeration (undercounter)



access valve convenient for service



safety design



special coating durable evaporator fins

ISO

Tropical Conditions

HOSHIZAKI



HOSHIZAKI GOLDLINE

Through intensive research and the application of Hoshizaki's original technology, the GOLDLINE series is available as a refrigerator or freezer in undercounters and upright reach-in types. The diverse options ranging from single, double or split doors for upright reach-in and double or triple door for undercounters makes the GOLDLINE range appealing to customers' various needs.

GOLDLINE SERIES

GOLDLINE SERIES
HOSHIZAKI
Refrigerator & Freezer

DIMENSIONS & SPECIFICATION

REFRIGERATOR
> **RTC-180SDA**
> **RTC-180SNA**

FREEZER
> **FTC-180SDA**
> **FTC-180SNA**



All **HOSHIZAKI GOLD LINE UNDERCOUNTER UNITS** are fitted and manufactured with the Standard Technical data:

- Temperature control: Refrigerators: -6°C to 12°C | Freezers : -25°C to -7°C
- Digital temperature controller
- Defrost system - Glass Tube heater
- Refrigerant - Refrigerator (R134a) | Freezer (R404a)
- Construction:
  - SUS 304 & SUS 430 for interior & exterior
  - Galvanised steel for rear & button
- Waste hose drain system
- Adjustable leg : (150-180 mm)
- Glass door options available

750MM DEPTH UNIT	CHILLER	FREEZER	CHILLER	FREEZER	CHILLER	FREEZER
MODEL	RTC-120 SDA	FTC-120 SDA	RTC-150 SDA	FTC-150 SDA	RTC-180 SDA	FTC-180 SDA
AMP	1.2A	2.2 A	1.5A	3.2 A	1.7 A	3.1 A
ELECTRICAL CONSUMPTION	193 W	408 W	271 W	543 W	314 W	582 W
HEAT REJECTION	310 W	680 W	480 W	1070 W	500 W	1070 W
WEIGHT IN KG (NETT/GROSS)	85 / 90	91 / 96	102 / 107	105 / 110	117 / 123	120 / 126
EXTERNAL DIMENSION (MM)	W1200 x D750 x H850		W1500 x D750 x H850		W1800 x D750 x H850	
INTERNAL DIMENSION (MM)	W830 x D577 x H588		W1130 x D577 x H588		W1430 x D577 x H588	
PACKED DIMENSION (MM)	W1265 x D830 x H790		W1565 x D830 x H790		W1865 x D830 x H790	
STORAGE CAPACITY (LITERS)	301		413		524	
DOOR /SHELF	2 DOORS / 2 PCS		2 DOORS / 2 PCS		3 DOORS / 3 PCS	

• **WARRANTY:**
1 year parts & labour on entire unit

OPERATING CONDITIONS: *• Voltage Range: 207V-254V • Ambient Temperature: 5°C to 43°C*
• AC Supply Voltage: 1/220-240V / 50 Hz

600MM DEPTH UNIT	CHILLER	FREEZER	CHILLER	FREEZER	CHILLER	FREEZER
MODEL	RTC-120 SNA	FTC-120 SNA	RTC-150 SNA	FTC-150 SNA	RTC-180 SNA	FTC-180 SNA
AMP	1.2A	2.2 A	1.5A	3.2 A	1.7 A	3.1 A
ELECTRICAL CONSUMPTION	193 W	408 W	271 W	543 W	314 W	582 W
HEAT REJECTION	310 W	680 W	480 W	1070 W	500 W	1070 W
WEIGHT IN KG (NETT/GROSS)	78 / 83	84 / 89	93 / 98	95 / 100	108 / 114	111 / 117
EXTERNAL DIMENSION (MM)	W1200 x D600 x H850		W1500 x D600 x H850		W1800 x D600 x H850	
INTERNAL DIMENSION (MM)	W830 x D427 x H588		W1130 x D427 x H588		W1430 x D427 x H588	
PACKED DIMENSION (MM)	W1265 x D680 x H790		W1565 x D680 x H790		W1865 x D680 x H790	
EFFECTIVE CAPACITY (LITERS)	228		313		398	
DOOR /SHELF	2 DOORS / 2 PCS		2 DOORS / 2 PCS		3 DOORS / 3 PCS	

• **WARRANTY:**
1 year parts & labour on entire unit

OPERATING CONDITIONS: *• Voltage Range: 207V-254V • Ambient Temperature: 5°C to 43°C*
• AC Supply Voltage: 1/220-240V / 50 Hz

R1

REACH-IN UNIT FAN SYSTEM



DC fan motor generates less heat than conventional AC motor over 80%



Compact fan motor unit



Energy saving computer controlled frame heater


UNDERCOUNTER UNIT

> **RTC-180SDA / RTC-180SNA (REFRIGERATOR)**
> **FTC-180SDA / FTC-180SNA (FREEZER)**


- Our undercounter models are designed with a compact refrigeration unit built in, while still performing at its optimum.
- It saves up to nearly 20% additional space when compared to others and allows the user more storage space.



UNDERCOUNTER AIR SYSTEM



BOTTOM SIDE



All **HOSHIZAKI GOLD LINE UPRIGHT UNITS** are fitted and manufactured with the Standard Technical data:

- Temperature control: Refrigerators: -6°C to 12°C | Freezers : -25°C to -7°C
- Evaporator system: Fin & Tube
- Defrost system: Refrigerator : Off cycle | Freezers: Heater
- Refrigerant - Refrigerator (R134a) & Freezer (R404a)
- Construction: SUS 304 & SUS 430 for interior & exterior. Galvanised steel for rear & bottom
- Adjustable leg: (150-180 mm)
- Glass door options are available.

MODEL (REFRIGERATORS)	HRE-77B	HRE-127B	HRE-147B	HRE-187B
AMP	2.08A	2.94A	2.94A	2.94A
ELECTRICAL CONSUMPTION	348 W	501 W	501 W	501 W
HEAT REJECTION	535 W	940 W	940 W	940 W
WEIGHT IN KG (NETT/GROSS)	111 / 126	132 / 158	152 / 177	203 / 250
EXTERNAL DIMENSION (MM)	W700 x D800 x H2050	W1200 x D800 x H2050	W1400 x D800 x H2050	W1800 x D800 x H2050
INTERNAL DIMENSION (MM)	W596 x D646 x H1484	W1096 x D646 x H1484	W1296 x D646 x H1484	W1696 x D646 x H1484
PACKED DIMENSION (MM)	W760 x D900 x H2075	W1260 x D900 x H2075	W1460 x D900 x H2075	W1860 x D900 x H2075
STORAGE CAPACITY (LITERS)	599	1109	1311	1720
DOOR /SHELF	2 DOORS / 4 PCS	4 DOORS / 8 PCS	4 DOORS / 8 PCS	6 DOORS / 12 PCS

• **WARRANTY:**
1 year parts & labour on entire unit

OPERATING CONDITIONS: *• Voltage Range: Rated Voltage ±6% • Ambient Temperature: 5°C to 43°C*
• AC Supply Voltage: 1/220-240V / 50 Hz

MODEL (FREEZERS)	HFE-77B	HFE-127B	HFE-147B	HFE-187B
AMP	3.51A	3.79A	3.79A	3.79A
ELECTRICAL CONSUMPTION	572 W	723 W	723 W	723 W
HEAT REJECTION	735 W	1330 W	1304 W	1330 W
WEIGHT IN KG (NETT/GROSS)	111 / 126	140 / 168	162 / 187	213 / 260
EXTERNAL DIMENSION (MM)	W700 x D800 x H2050 (-2080)	W1200 x D800 x H2050 (-2080)	W1400 x D800 x H2050 (-2080)	W1800 x D800 x H2050 (-2080)
INTERNAL DIMENSION (MM)	W596 x D646 x H1484	W1096 x D646 x H1484	W1296 x D646 x H1484	W1696 x D646 x H1484
PACKED DIMENSION (MM)	W760 x D900 x H2075	W1260 x D900 x H2075	W1460 x D900 x H2075	W1860 x D900 x H2075
STORAGE CAPACITY (LITERS)	599	1100	1304	1713
DOOR /SHELF	2 DOORS / 4 PCS	4 DOORS / 8 PCS	4 DOORS / 8 PCS	6 DOORS / 12 PCS

• **WARRANTY:**
1 year parts & labour on entire unit

OPERATING CONDITIONS: *• Voltage Range: Rated Voltage ±6% • Ambient Temperature: 5°C to 43°C*
• AC Supply Voltage: 1/220-240V / 50 Hz

R1